




Screens



Zonwering

CODE	BESCHRIJVING	STUKS/VERP.	CERTIFICERINGEN
E STAR MT 426	4 Nm, 26 rpm	1	NF CE
E STAR MT 1026	10 Nm, 26 rpm	1	NF CE
E STAR MT 817	8 Nm, 17 rpm	1	NF CE
E STAR MT 1517	15 Nm, 17 rpm	1	NF CE
E STAR MT 3017	30 Nm, 17 rpm	1	NF CE
E STAR MT 4012	40 Nm, 12 rpm	1	NF CE
E STAR MT 5012	50 Nm, 12 rpm	1	NF CE

TECHNISCHE KENMERKEN

CODE	E STAR MT 426	E STAR MT 1026	E STAR MT 817	E STAR MT 1517	E STAR MT 3017	E STAR MT 4012	E STAR MT 5012
ELEKTRISCHE GEGEVENS							
VOEDING (Vac/Hz)	230/50	230/50	230/50	230/50	230/50	230/50	230/50
STROOMOPNAME (A)	0,50	0,78	0,55	0,75	1,10	1,10	1,10
VERMOGEN (W)	108	150	120	170	250	245	250
GEABSORBEERD VERMOGEN STANDBY (W)	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5
PRESTATIEGEGEVENS							
KOPPEL (Nm)	4	10	8	15	30	40	50
SNELHEID (rpm)	26	26	17	17	17	12	12
AANTAL OMVENTELINGEN VÓÓR DE STOP	92	92	92	92	92	92	92
WERKINGSTIJD (min)	4	4	4	4	4	4	4
DIMENSIONALE GEGEVENS							
LENGTE (L) (mm)	426	451	426	451	486	486	486
GEWICHT VAN DE MOTOR (kg)	1,85	1,95	2,15	2,45	2,65	2,65	2,65
AFMETINGEN VERPAKKING (mm)	90x90x465	90x90x500	90x90x465	90x90x500	90x90x530	90x90x530	90x90x530

Beschermingsgraad IP44

Lengte kabel 2,5 m, 4 draden in de kabel



AFMETINGEN

