



Rolluiken



Zonwering



Zonneschermen met luifel



Rolpoorten

CODE	BESCHRIJVING	CERTIFICERINGEN
E XLH 12012	120 Nm, 12 rpm	CE
E XLH 15012	150 Nm, 12 rpm	CE
E XLH 18012	180 Nm, 12 rpm	CE
E XLH 23012	230 Nm, 12 rpm	CE
E XLH 30012	300 Nm, 12 rpm	CE

TECHNISCHE KENMERKEN

CODE	E XLH 12012	E XLH 15012	E XLH 18012	E XLH 23012	E XLH 30012
ELEKTRISCHE GEGEVENS					
VOEDING (Vac/Hz)	230/50	230/50	230/50	230/50	230/50
STROOMOPNAME (A)	3,4	3,5	3,7	3,9	5,4
VERMOGEN (W)	700	740	780	810	1250
PRESTATIEGEGEVENS					
KOPPEL (Nm)	120	150	180	230	300
SNELHEID (rpm)	12	12	12	12	12
OPGEHEVEN GEWICHT* (kg)	162	203	243	311	405
AANTAL OMWENTELINGEN VÓÓR DE STOP	36	36	36	36	36
WERKINGSTIJD (min)	6	6	6	5	5
DIMENSIONALE GEGEVENS					
LENGTE (L) (mm)	639/626	639/626	639/626	639/626	679/666
GEWICHT VAN DE MOTOR (kg)	13,4	11,8	11,8	11,2	13,8
AFMETINGEN VERPAKKING (mm)	750x210x210	750x210x210	750x210x210	750x210x210	750x210x210

*Waarde met achthoekige rol met diameter 108 mm. Beschermingsgraad IP44.

Lengte kabel 3 m, 4 draden in de kabel



AFMETINGEN

